

ASSEMBLY INSTRUCTION

ITEM# 33053

1. Fasten mounting strip onto outlet box using 2 outlet box screws.
2. Thread 2-1/8" nipple into center hole of mounting strip about 4 complete turns. Lock in place with lock washer and hex nut. This nipple should extend long enough to protrude through the canopy when it is mounted. Adjust as necessary.
3. Thread nipple into bushing of fixture body and secure with nut.
4. Position pipe, pipe lid, arm, cover over the nipple.
5. Guide supply wire through the loop, and secure loop onto the nipple.
6. Using two pliers, twist open one link at the end of chain links, Hook it to the loop and close the link. Place a piece of cloth between the pliers jaws and the chain link to prevent scratching the link finish.
7. Tighten the screw collar loop to the nipple on the mounting strip. Place the ring and canopy over the chain on the fixture. Using two pliers twist open the link at the other end of the chain. Hook the whole fixture to hook the screw collar loop on the ceiling and close the link.
8. Weave the fixture wires up through the chain links, through the screw collar loop and through the nipple in the mounting strip. Position both the outlet box supply wires and the fixture wires and fixture wires outside of the outlet box to facilitate connection. After connection (step 9) is complete, carefully position black wires inside outlet box.
9. Connect the wire from the fixture to the power supply wire from outlet box. Cover with wire connectors.
 - a) Twist together glossy wire from the fixture with white wire from outlet box. Cover with wire connectors.
 - b) Twist together rough wire from the fixture with black wire from outlet box. Cover with wire connectors.
 - c) Wrap the bare ground wire from the fixture and the outlet box around the green ground screw located on the mounting strip. Tighten the green ground screw to the mounting strip.
10. Place the canopy all the way to the ceiling, and tighten the ring onto the screw collar loop until the canopy is firmly held against the ceiling.
11. Thread finial into the connector of the fixture body.
12. Install bulbs (not included) into the sockets. Do not use greater than 40-watt bulbs.
13. Remove the plastic from the fabric shade.
14. Open the frame of the fabric shade to facilitate positioning onto the bulb. Remove the plug cover.
15. Hang ornament crystal to small ring of arm and socket cover.
16. Hang crystal chain to between small ring of socket cover.
17. Restore electric power, and test your new fixture.

PACKAGE PART

Wire connector	2	candle	6
Mounting strip	1	Fabric shade	6
Lock washer	1	Nipple	1
Hex nut	1	Finial	1
Green ground screw	1	Crystal chain	6
Outlet box screw	2	Ornament crystal	39
2-1/8" Nipple	1		
Screw collar loop	1		
Ring	1		
Chain	1		

